

Material Safety Data Sheet

Date prepared: June 16, 2004

Date Revised: October 18, 2007

1. PRODUCT IDENTIFICATION

Product name: EZCLEAR Detailer's All-Spray
 Company information: Plastek LLC
 3300 Industry Drive
 Signal Hill, CA 90755
 Emergency # (650)367-7075
 Information #: 650-367-7075
 www.PlastekLLC.com

2. HAZARDOUS INGREDIENTS: Principle Hazardous Component(s)

NAME	PERCENT	THRESHOLD LIMIT /VALUE (UNITS)
Proprietary Information	15%	NR
None of these components are hazardous as defined by 29CFR1910, 1200, OSHA's Hazard Communications Standard		
	2%	NR
OTHER INGREDIENTS		
Water (CAS #7732-18-5)	83%	Not applicable

3. PHYSICAL AND CHEMICAL CHARACTERISTICS (Fire & Explosion Data)

Boiling Point	212* Fahrenheit
Specific Gravity (H2O=1)	1
Vapor Pressure (MM Hg)	Approximately 20
Percent Volatile by Volume (%)	Almost all
Vapor Density (Air = 1)	Same as water (approximately 0.7)
Evaporation Rate	Same as water (low)
Solubility in Water	Highly soluble
Reactivity in Water	N/A
Appearance and Odor	Milky white liquid, very little odor

4. FIRE AND EXPLOSION DATA

Flash Point	N/A
Flammable Limits in Air % By Volume	Lower N/A, Upper N/A
Extinguisher Media	Water spray, dry chemical, carbon dioxide or foam as appropriate for surrounding fire and materials.
Auto Ignition Temperature	N/A
Special Fire Fighting	As with all fires, evacuate personnel to a safe area. Fire fighters should use self-contained breathing equipment and protective clothing.
Unusual Fire and Explosion Hazards	None known

5. PHYSICAL HAZARDS

Stability	() Unstable (X) Stable
Conditions to Avoid	Material is stable from a safety point of view.
Incompatibility (Materials to Avoid)	Oxidizing materials may cause a reaction
Hazardous Decomposition Products	Silicon dioxide, carbon dioxide, and traces of incompletely burned carbon products.
Hazardous Polymerization	Will not occur

6. HEALTH HAZARDS

Routes of Entry	Inhalation, skin, accidental ingestion, skin injection
Threshold Limit Value	None established.
Signs and Symptoms of Over Exposure	Liquid is largely inert in contact with the human system. It may cause mild eye irritation upon eye contact or upon injection into the eye. Care should be used in using this material with any pressurized systems. Methyl Paraben can cause sensitization reactions and dermatitis in sensitive individuals.
Medical Conditions Aggravated by Exposure	Hyper-sensitivity to the material.
Emergency and First Aid Procedures	Upon eye or skin contact, flush affected area with water. Obtain medical attention.
Carcinogenicity	None reported by OSHA, IARC, or NTP

7. SPECIAL PROTECTION INFORMATION

Respiratory Protection	None required.
Ventilation	Ventilation should be used to maintain exposure below the PEL and TLV
Protective Gloves	Rubber or vinyl gloves can be used if employees experience skin irritation.
Eye Protection	Safety goggles should be worn when splash hazards are present.
Other Protective Clothing or Equipment	Protect exposed skin. Appropriate laboratory apparel.

8. SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Precautions To Be Taken In Handling And Storage	Keep from freezing. This material should be handled and stored per label and other instructions to ensure product integrity.
Other Precautions	Exercise care in using this material with any pressurized systems offering potential for eye or skin injection.
Steps To Be Taken In Case Material Is Spilled Or Released	Use absorbent material to collect and contain material for salvage or disposal.
Waste Disposal Methods	Dispose of waste in accordance with all applicable Federal, State, and Local Laws.

N/A – Not Applicable

N/R – Not Regulated